

Corflute® Supermarket Range

We hold 7 Corflute® colours in stock including; White, Red, Blue, Yellow, Green, Grey & Black.

Our “off-the-shelf” Supermarket Range is suitable for people looking for smaller quantities (multiple packs of 10 and 15 sheets).

Make a product from Corflute®

Want a product made from our Supermarket Range? Our creative team can work with you to create boxes, containers and other custom-made products.

Technical information & options:

- **Material:** 100% recyclable Australian made polypropylene
- **Printability:** Corona surface treatment applied to enable ink adhesion. Ideal for screen and digital printing
- **Wettability:** Unaffected by water. Ideal for outdoor signage
- **UV stabilised:** For outdoor applications
- **Surface temperature:** Retains integrity between minus 20 degrees C to 85 degrees C

Thickness:

- Gauge: 2.5, 3, 4 & 5mm
- Weight: 350gsm – 850gsm

Standard Sizes:

- 900 x 600 mm
- 900 x 1200 mm

Other sizes available cut to size from stock sheet.

*MOQ's apply

Refer to website for more sizes and MOQ's - [full details here>](#)

Colours:

- White, Red, Blue, Yellow, Green, Grey & Black



Learn more about the Corflute® Supermarket Range [here >](#)

Corflute®

VER0907COR

MATERIAL PROPERTIES	UNIT	VALUE	TEST METHOD
Mechanical & Physical Properties			
Specific Gravity	g/cc	0.91-0.925	ASTM D792
Tensile Strength @ Yield	MPa	25	ASTM D638
Flexural modulus	GPa	1.1	ASTM D790
Elongation @ break	%	≥700	ASTM D638
Izod Impact	J/m	134	ASTM D256
Izod Impact @ 23° Celsius	KJ/m ²	14	ISO 180/1
Izod Impact @ 0° Celsius	KJ/m ²	6.5	ISO 180/1
Izod Impact @ -23° Celsius	KJ/m ²	4	ISO 180/1
Drop Dart Impact	Kg cm/mm	50	Nylex TM4
Heat deflection temp @ 1.82 MPa	°C	50	ASTM D648
Hardness	Shore D	68	ASTM D2240
Linear coefficient of thermal expansion	mm/mm/°C	10-15x10 ⁻⁵	ASTM D696
Mould shrinkage	%	1-2	ASTM D955

GENERAL INFORMATION

Standard Gauges (mm)	3mm-10mm	Standard Sheet Size (mm)	2440mm x 1220mm
Finish	Corona treated	Printable	Yes
Colour	Any colour	U.V. Treatment	Yes
Service Temp	-20°C to +95°C	Warranty	Tested to 3 year outdoor weathering

Corex Plastics (Australia) Pty. Ltd.

261 Frankston Dandenong Road, Dandenong 3175 AUSTRALIA

 Phone: +61 3 9238 1300 Email: info@corex.com.au

* All information is to the best of our knowledge, true and correct. However, as many factors outside our knowledge and control can effect the products, no warranty can be given or implied in respect of such information and no information should be construed as a warranty in relation to the product or its use.

CODE: CL_1116

 Find out more
corex.com.au